

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number  
**WO 02/064532 A2**

(51) International Patent Classification<sup>7</sup>: C07C 11/02,  
5/333, 303/24, 29/16, 31/02, C11D 1/12, C07C 9/00

(21) International Application Number: PCT/EP02/01700

(22) International Filing Date: 15 February 2002 (15.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/269,874 15 February 2001 (15.02.2001) US

(71) Applicant: SHELL INTERNATIONALE RESEARCH  
MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan  
30, NL-2596 HR The Hague (NL).

(72) Inventors: AYOUB, Paul, Marie; 7438 Shangrila Lane,  
Houston, TX 77095 (US). FENOUIL, Laurent, Alain; 2  
York Road, Waterloo, London SE1 7NA (GB). MURRAY,  
Brendan, Dermot; 1118 Stoney Hill Drive, Houston, TX  
77077 (US).

(74) Agent: SHELL INTERNATIONAL B.V.; Intellectual  
Property Services, P.O. Box 384, NL-2501 CJ The Hague  
(NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN,  
YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent  
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,  
NE, SN, TD, TG).

**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: A PROCESS FOR PREPARING A BRANCHED OLEFIN, A METHOD OF USING THE BRANCHED OLEFIN FOR MAKING A SURFACTANT, AND A SURFACTANT

(57) Abstract: A process for preparing branched olefins which process comprises dehydrogenating an isoparaffinic composition comprising 0.5 % or less quaternary aliphatic carbon atoms over a suitable catalyst, which isoparaffinic composition comprises paraffins having a carbon number in the range of from 7 to 35, of which paraffins at least a portion of the molecules is branched, the average number of branches per paraffin molecule being from 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, and which isoparaffinic composition may be obtained by hydrocracking and hydroisomerisation of a paraffinic wax, said branched olefins having a quaternary carbon content of 0.5 % or less; a process of using olefins for making an anionic surfactant, a nonionic surfactant or a cationic surfactant, in particular a surfactant sulphate or sulphonate, comprising converting the branched olefins into the surfactant, and an anionic surfactant, a nonionic surfactant or a cationic surfactant which is obtainable by said process.

WO 02/064532 A2

- 1 -

A PROCESS FOR PREPARING A BRANCHED OLEFIN,  
A METHOD OF USING THE BRANCHED OLEFIN FOR MAKING  
A SURFACTANT, AND A SURFACTANT

FIELD OF THE INVENTION

This invention relates to a process for preparing a branched olefin, to a method of using the branched olefin for making a surfactant, and to the surfactant per se.

5 BACKGROUND OF THE INVENTION

US-A-5849960 relates to surfactant sulphates based on branched alcohols. The branched alcohols in question have an average number of branches per molecule chain of at least 0.7. The branching comprises not only methyl  
10 branching but also ethyl branches, whilst the occurrence of longer branching is not excluded. The branched alcohols are made from branched olefins, which are made by skeletally isomerising linear olefins. The surfactant sulphates of US-A-5849960 simultaneously satisfy  
15 requirements for biodegradability, cold water solubility and cold water detergency.

The market always asks for improvements in the performance of existing detergent formulations, inter alia by improving the surfactants present in the  
20 detergent formulations. For example, the laundry market asks for improvements in the surfactants' biodegradability, their cold water solubility and their cold water detergency. At least an improvement is sought in the balance of the properties. By the terminology "an  
25 improvement in the balance of the properties" it is meant that at least one property is improved, whilst at least one of the other properties is not deteriorated.

The present invention seeks to provide improvements in the performance of the surfactant sulphates of US-A-

- 2 -

5849960, or at least in an improvement in the balance of their performance properties. Relevant performance properties are biodegradability, cold water solubility and cold water detergency, for example cold water  
5 detergency in water of low hardness and in water of high hardness. Other relevant performance properties are the compatibility of the surfactant sulphates with other components present in detergent formulations, as described hereinafter, in particular, the compatibility  
10 with enzymes, i.e. the inability of the surfactant sulphates to denature enzymes during storage in an aqueous medium. Again other relevant performance properties, in particular for personal care applications, are mildness to the skin and to the eyes and the ability  
15 of high foaming, preferably providing foam with a fine structure of the foam cells. Further, an improved performance is sought as a chemical for enhanced oil recovery applications and for the removal of oil spillage, viz. an improved ability to emulsify oil/water  
20 and oil/brine systems and to stabilize emulsions of oil and water or brine, in particular at high temperature. Independently, the present invention seeks to provide a method for the manufacture of surfactant sulphates which is more versatile and economically more attractive than  
25 the method known from US-A-5849960. In analogy, the invention seeks to provide similar improvements with respect to anionic surfactants, non-ionic surfactants and cationic surfactants, other than the surfactant sulphates mentioned hereinbefore, and their methods of manufacture.

- 3 -

SUMMARY OF THE INVENTION

In accordance with this invention surfactant sulphates are prepared by dehydrogenating selected branched paraffins to produce branched olefins. These  
5 branched olefins can be converted into branched alcohols and subsequently into surfactant sulphates. Alternatively, the branched olefins can be converted into other surfactant types, in particular anionic surfactants other than the surfactant sulphates, such as surfactant  
10 sulphonates; nonionic surfactants and cationic surfactants. It is an advantage of this invention that surfactants and intermediates can be made with a very low content of molecules, which have a linear carbon chain. It is another advantage of the invention that products  
15 can be made of which the molecules have a low content of branches having three or more carbon atoms. It is also an advantage of the invention that products can be made of which the molecules have a low content of quaternary aliphatic carbon atoms. Without wishing to be bound by  
20 theory, it is believed that the presence of quaternary aliphatic carbon atoms in the molecules of the surfactants prevents to some extent their biodegradation and the presence of quaternary aliphatic carbon atoms in the isoparaffinic composition is therefore preferably  
25 avoided. In fact, it has been determined that the presence of 0.5% or less quaternary aliphatic carbon atoms in the molecules of the surfactants renders the surfactants substantially more biodegradable.

Accordingly, the present invention provides a  
30 process for preparing branched olefins, which process comprises dehydrogenating an isoparaffinic composition comprising 0.5% or less quaternary aliphatic carbon atoms over a suitable catalyst, which isoparaffinic composition comprises paraffins having a carbon number in  
35 the range of from 7 to 35, of which paraffins at least a

- 4 -

portion of the molecules is branched, the average number of branches per paraffin molecule being from 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, which isoparaffinic composition has been  
5 obtained by hydrocracking and hydroisomerisation of a paraffinic wax, said branched olefins having a quaternary carbon content of 0.5% or less.

The present invention also provides a process of using olefins for making an anionic surfactant, a  
10 nonionic surfactant or a cationic surfactant, in particular a surfactant sulphate or sulphonate, comprising converting branched olefins into the surfactant which branched olefins have been obtained in accordance with the present invention. In particular,  
15 the present invention provides a process for preparing alcohol sulphates comprising converting branched olefins into branched alcohol sulphates, which branched olefins have been obtained by a process which comprises dehydrogenating an isoparaffinic composition comprising  
20 0.5% or less quaternary aliphatic carbon atoms over a suitable catalyst, which isoparaffinic composition comprises paraffins having a carbon number in the range of from 7 to 35, of which paraffins at least a portion of the molecules is branched, the average number of branches  
25 per paraffin molecule being from 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, said alcohol sulphates comprising 0.5% or less quaternary aliphatic carbon atoms.

Further, the invention provides a process for  
30 preparing alcohol sulphates, comprising converting branched olefins into branched alcohol sulphates which branched olefins have been obtained in accordance with this invention.

In a further aspect the present invention provides a  
35 branched olefin composition comprising olefins having

- 5 -

different, consecutive carbon numbers in the range of from 7 to 35, of which olefins at least a portion of the molecules is branched, the average number of branches per molecule being at least 0.7 and the branching comprising methyl and optionally ethyl branches. In particular, the present invention provides a branched olefin composition having 0.5% or less quaternary carbon atoms and comprising olefins having different, consecutive carbon numbers in the range of from 7 to 35, of which olefins at least a portion of the molecules is branched, the average number of branches per molecule being 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, and which branched olefin composition is obtainable by a process which comprises dehydrogenating an isoparaffinic composition which has been obtained by hydrocracking and hydroisomerisation of a paraffinic wax, said isoparaffinic composition comprising less than 0.5% quaternary aliphatic carbon atoms.

In again a further aspect the present invention provides a branched alcohol composition which is obtainable by a process according to the present invention, e.g. comprising reacting branched olefins according to the present invention with carbon monoxide and hydrogen, preferably in the presence of a suitable catalyst.

In again a further aspect the present invention provides an anionic surfactant, a nonionic surfactant and a cationic surfactant, in particular a surfactant sulphate or sulphonate, which is obtainable by a method of use in accordance with this invention.

In again a further aspect the present invention provides an isoparaffinic composition comprising less than 0.5% quaternary aliphatic carbon atoms and comprising paraffins having different, consecutive carbon numbers in the range of from 7 to 35, of which paraffins

- 6 -

at least a portion of the molecules is branched, the average number of branches per paraffin molecule being from 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches.

5           In again a further aspect the invention provides a branched olefin composition which is obtainable in accordance with the present invention.

          Without wishing to be bound by theory, it is believed that any improvement in the performance  
10       properties of the surfactant sulphates prepared in accordance with this invention, compared with the surfactant sulphates specifically known from US-A-5849960, resides in a difference in the distribution of branching along the respective paraffinic chains. Such  
15       differences in the distribution of branching are truly unexpected in view of the prior art and, therefore, they are inventive.

#### DETAILED DESCRIPTION OF THE INVENTION

          As described herein, the isoparaffinic composition  
20       and the compositions of branched olefins and alcohols derived therefrom are generally mixtures comprising molecules with different, consecutive carbon numbers. Typically at least 75 %w, more typically at least 90 %w, of these compositions represent a range of molecules of  
25       which the heaviest molecules comprises at most 6 carbon atoms more than the lightest molecules.

          The isoparaffinic composition comprises paraffins having a carbon number in the range of from 7 to 35, of which paraffins at least a portion of the molecules is  
30       branched. Preferably, the isoparaffinic composition comprises paraffins having a carbon number in the range of from 10 to 18. Preferably at least 75 %w, more preferably at least 90 %w, of the isoparaffinic composition consists of paraffins having a carbon number  
35       in the range of from 10 to 18. In practice, frequently

- 7 -

at most 99.99 %w, more frequently at most 99.9 %w, of the isoparaffinic composition consists of paraffins having a carbon number in the range of from 10 to 18. When it is intended to prepare surfactant sulphates from the isoparaffinic composition it is preferred that the isoparaffinic composition comprises paraffins having a carbon number in the range of from 14 to 17, in which case preferably at least 75 %w, more preferably at least 90 %w, of the isoparaffinic composition consists of paraffins having a carbon number in the range of from 14 to 17. In practice, frequently at most 99.99 %w, more frequently at most 99.9 %w, of the isoparaffinic composition consists of paraffins having a carbon number in the range of from 14 to 17. These selections are based on the effects that the paraffins of a lower carbon number ultimately yield surfactants which are more volatile and that the paraffins of a higher carbon number ultimately yield surfactants with less water solubility.

The average number of branches per paraffin molecule present in the isoparaffinic composition is at least 0.7, calculated over the total of the branched paraffins and, if present, the linear paraffins. Suitably the average number of branches is at least 0.8, and preferably at least 0.9, for example 1.0. Suitably the average number of branches is at most 2.0, preferably at most 1.5, and in particular at most 1.4. On the other hand, for some applications it may be desirable that the average number of branches is at least 1.5 and suitably at most 2.5.

The number of methyl branches present in the isoparaffinic composition is suitably at least 20%, more suitably at least 40%, preferably at least 50% of the total number of branches. In practice the number of methyl branches is frequently at most 99%, more frequently at most 98% of the total number of branches. If present, the number of ethyl branches is suitably at



- 8 -

least 0.1%, in particular at least 1%, more in particular at least 2% of the total number of branches. Suitably, the number of ethyl branches is at most 20%, in particular at most 15%, more in particular at most 10% of the total number of branches. The number of any branches, if present, other than methyl and ethyl branches, may be less than 10%, in particular less than 5% of the total number of branches. The number of any branches, if present, other than methyl and ethyl branches, may be more than 0.1%, typically more than 1% of the total number of branches.

The number of quaternary aliphatic carbon atoms present in the isoparaffinic composition is preferably low. For applications where biodegradability is not as critical, the number of quaternary aliphatic carbon atoms is suitably less than 2% of the carbon atoms present, more suitably less than 1%. For any application, and particularly for applications where biodegradability is important, the number of quaternary aliphatic carbon atoms preferably is 0.5 % or less, most preferably less than 0.5 %, and in particular less than 0.3%. In practice the number of quaternary aliphatic carbon atoms present in the isoparaffinic composition is frequently more than 0.01% of the aliphatic carbon atoms present, more frequently more than 0.05%.

The content of branched paraffins of the isoparaffinic composition is typically at least 70%w, more typically at least 90%w, preferably at least 95%w, more preferably at least 99%w, in particular at least 99.9%w, relative to the weight of the isoparaffinic composition. In practice the content of branched paraffins is frequently at most 99.99%w, more frequently at most 99.95%w, relative to the weight of the isoparaffinic composition. The content of linear paraffins of the isoparaffinic composition is typically

- 9 -

at most 30%w, more typically at most 10%w, preferably at most 5%w, more preferably at most 1%w, in particular at most 0.1%w, relative to the weight of the isoparaffinic composition. In practice the content of linear paraffins is frequently at least 0.01%w, more frequently at least 0.05%w, relative to the weight of the isoparaffinic composition.

The isoparaffinic composition may originate from various sources. For example, suitable isoparaffinic compositions may be selected from crude oil distillation fractions. Such crude oil distillation fractions may be treated to partially or, more preferably, completely remove sulphur and/or nitrogen containing components.

Alternatively, the isoparaffinic composition may be obtained by hydroisomerisation of a paraffinic composition, i.e. a composition which comprises predominantly linear paraffins, such as obtainable from a Fischer Tropsch process or from an ethylene oligomerisation process. Linear paraffins obtained in a Fischer Tropsch synthesis are particularly preferred because Fischer Tropsch products are generally very low in their content of sulphur and nitrogen and they are cost effective. The Fischer Tropsch products may or may not comprise oxygenates. The product obtained in the hydroisomerisation process may be fractionated, for example, by distillation or otherwise, in order to isolate an isoparaffinic product of the desired composition. Such a hydroisomerisation process and subsequent fractionation is known, for example from US-A-5866748.

Preferably, the isoparaffinic composition is obtained by hydrocracking and hydroisomerisation of a paraffinic wax, in particular a slack wax, a wax obtained in a Fischer Tropsch synthesis or a polyethylene wax. The paraffinic wax comprises typically linear paraffins

- 10 -

having at least 5 carbon atoms, preferably at least 15 carbon atoms, more preferably at least 25 carbon atoms. In practice, the paraffinic wax comprises frequently linear paraffins of which the number of carbon atoms may  
5 be high, for example up to 100 or up to 200 and even more. Wax obtained in a Fischer Tropsch synthesis is particularly preferred because these are generally very low in their content of sulphur and nitrogen and they are cost effective. The product obtained in the  
10 hydrocracking/hydroisomerisation process may be fractionated, for example, by distillation or otherwise, in order to isolate an isoparaffinic product of the desired composition. Such a hydrocracking/hydroisomerisation process and subsequent fractionation is  
15 known, for example from US-A-5833839. Generally, the hydrocracking/hydroisomerisation process involves hydrocracking with simultaneous hydroisomerisation.

The isoparaffinic composition may be treated to lower the content of linear paraffins, in order to  
20 favorably adjust the average number of branches in the isoparaffinic composition. Such separation may be accomplished by separation using a molecular sieve as absorbent. The molecular sieve may be, for example, a zeolite 4A, a zeolite 5A, a zeolite X or a zeolite Y.  
25 Reference may be made to "Kirk-Othmer Encyclopedia of Chemical Technology", 4<sup>th</sup> edition, Volume 1, pp. 589-590, and Volume 16, pp. 911-916; and "Handbook of Petroleum Refining Processes" (R A Meyers, Ed.), 2<sup>nd</sup> edition, pp. 10.45-10.51, 10.75-10.77.

30 Catalysts suitable for the dehydrogenation of the isoparaffinic composition may be selected from a wide range. For example, they may be based on a metal or metal compound deposited on a porous support, the metal or metal compound being one or more selected for example  
35 from chrome oxide, iron oxide and, preferably, the noble

- 11 -

metals. The noble metals are understood to be the metals of the group formed by platinum, palladium, iridium, ruthenium, osmium and rhodium. Preferred noble metals are palladium and, in particular, platinum.

5           Suitable porous supports may be supports of a carbon nature such as activated carbon, coke and charcoal; silica or silica gel, or other natural or synthetic clays or silicates, for example hydrotalcites; ceramics; refractory inorganic oxides such as alumina, titania or  
10           magnesia; naturally or synthetic crystalline aluminosilicates such as mordenite or faujasite; and combinations of two or more elements selected from these groups. The porous support is preferably an alumina, in particular gamma alumina or eta alumina.

15           The quantity of the metal or metal compound deposited on the porous support is not material to this invention. The quantity may suitably be selected in the range of from 0.01 to 5 %w, preferably from 0.02 to 2 %w, based on the weight of the catalyst.

20           Further metals may be present in the catalyst used for the dehydrogenation of the isoparaffinic composition, in particular in the catalysts which comprise a noble metal. Such further metals may suitably be selected from Group 3a, Group 4a and Group 5a of the Periodic Table of  
25           Elements (cf. R C Weast (Ed,) "Handbook of Chemistry and Physics", 54<sup>th</sup> edition, CRC Press, inside cover). In particular, indium may be selected from Group 3a, tin may be selected from Group 4a or bismuth may be selected from Group 5a. Especially suitable further metals are alkali  
30           and alkaline earth metals. Preferred alkali metals are potassium, and in particular lithium.

          Further elements, which may be present in the catalyst used for the dehydrogenation of the isoparaffinic composition, are halogens, in particular in  
35           combination with a metal of Group 4a, more in particular

- 12 -

in combination with tin. Chlorine is a preferred halogen.

The quantity of such further metals or halogens may independently be in the range of from 0.01 to 5 %w, preferably from 0.02 to 2 %w, based on the weight of the catalyst.

Suitable catalysts for the dehydrogenation of the isoparaffinic composition are, for example, chrome oxide on gamma alumina, platinum on gamma alumina, palladium on gamma alumina, platinum/lithium on gamma alumina, platinum/potassium on gamma alumina, platinum/tin on gamma alumina, platinum/tin on hydrotalcite, platinum/indium on gamma alumina and platinum/bismuth on gamma alumina.

The dehydrogenation may be operated at a wide range of conditions. Suitably the temperature is in the range of from 300 °C to 700 °C, more suitably in the range of from 400 °C to 600 °C, in particular in the range of from 450 to 550 °C. The total pressure may be an elevated pressure, such as in the range of from 110 to 1500 kPa a (1.1 to 15 bara) (i.e. kPa or bar absolute), preferably in the range of from 130 to 1000 kPa a (1.3 to 10 bara), in particular in the range of from 150 to 500 kPa a (1.5 to 5 bara). In order to prevent coking, hydrogen may be fed together with the isoparaffinic composition. Suitably, hydrogen and paraffins present in the isoparaffinic composition are fed at a molar ratio in the range of from 0.1 to 20, more suitably this molar ratio is in the range of from 0.5 to 15, in particular this molar ratio is in the range of from 1 to 10.

The residence time in the dehydrogenation is typically selected such that conversion level of the isoparaffinic composition is kept below 50 mole-%, preferably in the range of from 5 to 30 mole-%, in particular in the range of from 10 to 20 mole-%. By

- 13 -

keeping the conversion level low, side reactions may to some extent be prevented, such as diene formation and cyclisation reactions. Non-converted paraffins and dehydrogenated compounds may be separated from the  
5 dehydrogenation product and, if desired, non-converted paraffins may be recycled to the dehydrogenation step. Such separation may be accomplished by extraction, by extractive distillation or, preferably, by using a molecular sieve as absorbent. The molecular sieve may  
10 be, for example, a zeolite 4A, a zeolite 5A, a zeolite X or a zeolite Y. If desired, linear olefins may be separated at least to some extent from branched olefin so that the content of branched olefin in the product as obtained from the dehydrogenation is increased further,  
15 but this option is generally not preferred.

The skilled person is aware of the techniques of preparing the catalysts, performing the dehydrogenation step and performing associated separation steps, for use in this invention. For example, suitable procedures for  
20 preparing catalysts and performing the dehydrogenation are known from US-A-5012021, US-A-3274287, US-A-3315007, US-A-3315008, US-A-3745112, US-A-4430517. For techniques suitable for the separation of branched olefins from linear olefins, reference may be made to "Kirk-Othmer  
25 Encyclopedia of Chemical Technology", 4<sup>th</sup> edition, Volume 1, pp. 589-591, and Volume 16, pp. 911-916; and "Handbook of Petroleum Refining Processes" (R A Meyers, Ed.), 2<sup>nd</sup> edition, pp. 10.45-10.51, 10.79-10.81.

The dehydrogenation in accordance with this  
30 invention yields typically a branched olefin composition comprising olefins having a carbon number in the range of from 7 to 35, of which olefins at least a portion of the molecules is branched, the average number of branches per molecule being at least 0.7 and the branching comprising  
35 methyl and optionally ethyl branches. Preferably, the

- 14 -

branched olefin composition comprises olefins having a carbon number in the range of from 10 to 18. Preferably at least 75%w, more preferably at least 90%w, of the branched olefin composition consists of olefins having a carbon number in the range of from 10 to 18. In practice, frequently at most 99.99%w, more frequently at most 99.9%w, of the branched olefin composition consists of olefins having a carbon number in the range of from 10 to 18. When it is intended to prepare surfactant sulphates from the branched olefin composition it is preferred that the branched olefin composition comprises olefins having a carbon number in the range of from 14 to 17, in which case preferably at least 75%w, more preferably at least 90%w, of the branched olefin composition consists of olefins having a carbon number in the range of from 14 to 17. In practice, frequently at most 99.99%w, more frequently at most 99.9%w, of the branched olefin composition consists of olefins having a carbon number in the range of from 14 to 17.

Suitably the average number of branches per olefin molecule present in the branched olefin composition is at least 0.8, and preferably at least 0.9, for example 1.0. Suitably the average number of branches is at most 2.0, preferably at most 1.5, and in particular at most 1.4. The number of methyl branches is suitably at least 20%, more suitably at least 40%, preferably at least 50% of the total number of branches. In practice the number of methyl branches is frequently at most 99%, more frequently at most 98% of the total number of branches. If present, the number of ethyl branches is suitably at least 0.1%, in particular at least 1%, more in particular at least 2% of the total number of branches. Suitably, the number of ethyl branches is at most 20%, in particular at most 15%, more in particular at most 10% of the total number of branches. The number of any

- 15 -

branches, if present, other than methyl and ethyl branches, may be less than 10%, in particular less than 5% of the total number of branches. The number of any branches, if present, other than methyl and ethyl  
5 branches, may be more than 0.1%, typically more than 1% of the total number of branches.

The number of quaternary aliphatic carbon atoms present in the branched olefins is preferably low. For applications where biodegradability is not as critical,  
10 the number of quaternary aliphatic carbon atoms is suitably less than 2% of the carbon atoms present, more suitably less than 1%. For any application, and particularly for applications where biodegradability is important, the number of quaternary aliphatic carbon  
15 atoms preferably is 0.5 % or less, most preferably less than 0.5 %, and in particular less than 0.3%. In practice the number of quaternary aliphatic carbon atoms present in the branched olefins is frequently more than 0.01% of the aliphatic carbon atoms present, more  
20 frequently more than 0.05%.

The content of branched olefins of the branched olefin composition is typically at least 70%w, more typically at least 90%w, preferably at least 95%w, more preferably at least 99%w, in particular at least 99.9%w,  
25 relatively to the weight of the branched olefin composition. In practice the content of branched olefins is frequently at most 99.99%w, more frequently at most 99.95%w, relatively to the weight of the branched olefin composition. The content of linear olefins of the  
30 branched olefin composition is typically at most 30%w, more typically at most 10%w, preferably at most 5%w, more preferably at most 1%w, in particular at most 0.1 %w, relatively to the weight of the branched olefin composition. In practice the content of linear olefins  
35 is frequently at least 0.01%w, more frequently at least



- 16 -

0.05%w, relative to the weight of the branched olefins composition.

The branched olefin composition is suitable for the manufacture of anionic, nonionic, and cationic  
5 surfactants, preferably the former two, more preferably the anionic surfactants.

More preferably, the branched olefin composition is used for the manufacture of surfactant sulphates, including alcohol sulphates and oxyalkylated alcohol  
10 sulphates, or nonionic oxyalkylated alcohols. To this end, the branched olefins may be converted into branched alcohols. Preferably, the branched alcohols are branched primary alcohols. As an alternative, the branched alcohols may be branched secondary alcohols.

15 Conversion of the branched olefins into branched alcohols is conveniently accomplished, for example, by hydroformylation, by oxidation and hydrolysis, by sulphation and hydration, by epoxidations and hydration, or the like.

20 In hydroformylation, the branched olefins are converted into primary branched alcohols by reaction with carbon monoxide and hydrogen in the presence of a suitable catalyst. Methods of hydroformylation which are suitable for use in this invention are known from, for  
25 example, US-A-3231621, US-A-3239566, US-A-3239569, US-A-3239570, US-A-3239571, US-A-3420898, US-A-3440291, US-A-3448158, US-A-3448157, US-A-3496203, US-A-3496204, US-A-3501515, US-A-3527818 and US-A-6037506. Further methods are described in Kirk Othmer, "Encyclopedia of  
30 Chemical Technology" 3<sup>rd</sup> edition. Vol. 16, pages 637-653; "Monohydric Alcohols: Manufacture, Applications and Chemistry", E J Wickson (Ed.), Am. Chem. Soc. 1981.

Hydroformylation is a term used in the art to denote the reaction of an olefin with carbon monoxide and  
35 hydrogen to produce an aldehyde or alcohol, which has one

- 17 -

more carbon atom than the reactant olefin. Frequently, in the art, the term hydroformylation is utilised to cover the aldehyde and the reduction to the alcohol step in total, i.e., hydroformylation refers to the production of alcohols from olefins via carbonylation and an aldehyde reduction process. As used herein, hydroformylation refers to the ultimate production of alcohols.

Suitable catalysts are based on a metal of Group 8 of the Periodic Table. Preferred metals of Group 8 may be selected from palladium, platinum, rhodium, nickel and cobalt, in particular from cobalt, rhodium and palladium. The Group 8 metal may or may not be used in the form of a complex compound in which the Group 8 is combined with a ligand, for example a phosphine, phosphite, arsine, stibine or pyridine ligand. Illustrative hydroformylation catalysts include cobalt hydrocarbonyl catalyst, cobalt-phosphine ligand catalyst, and rhodium-phosphine ligand catalyst.

The source of the Group 8 metal may be a salt. Preferred are salts of acids which have a pKa value of less than 6, in particular less than 4, more in particular less than 2, when measured in water at 20 °C. Examples of suitable acids are nitric acid, sulphuric acid, carboxylic acids and sulphonic acids. Preferred carboxylic acids are the  $\alpha$ -halocarboxylic acids, such as dichloroacetic acid, trifluoroacetic acid and perfluoropropionic acid. Preferred sulphonic acids are p-toluenesulphonic acid, benzenesulphonic acid and methanesulphonic acid.

It is also possible to employ as a source of the Group 8 metal the metallic element itself or a zero valence metal complex, for example a complex with carbon

- 18 -

monoxide. This would require, however, the additional presence of a protic acid.

With respect to the ligands, mention may be made of monophosphines which comprise three hydrocarbyl and/or hydrocarbyloxy groups attached to phosphorus, and the corresponding arsines and stibines. Examples of the monophosphines are triamylphosphine, trihexylphosphine, dimethylethylphosphine, diamylethylphosphine, tricyclopentylphosphine, tricyclohexylphosphine, diphenylbutylphosphine, diphenylbenzylphosphine, diphenyl(2-pyridyl)phosphine, phenyl[bis(2-pyridyl)]phosphine, triethoxyphosphine, butyldiethoxyphosphine, triphenylphosphine, dimethylphenylphosphine, methyldiphenylphosphine, dimethylpropylphosphine, and the tritolylphosphines.

Alternatively, bidentate ligands may be used such as tetrahydrocarbylbisphosphines or the corresponding arsines or stibines. Examples of tetrahydrocarbylbisphosphines are 1,2-bis(dimethylphosphino)ethane, 1,2- and 1,3-bis(dimethylphosphino)propane, 1,2-bis(diethylphosphino)ethane, 1,2-bis[di(1-butyl)phosphino]ethane, 1-dimethylphosphino-2-diethylphosphinoethane, 1,2-bis(diphenylphosphino)ethane, 1,2-bis(diperfluorophenylphosphino)ethane, 1,3-bis(diphenylphosphino)propane, 1,4-bis(diphenylphosphino)butane, 1-dimethylphosphino-2-diphenylphosphinoethane, 1-diethylphosphino-3-diphenylphosphinopropane and 1,2-bis[di(o-tolyl)phosphino]ethane.

Other suitable ligands are the phosphabicyclohydrocarbons, such as 9-hydrocarbyl-9-phosphabicyclononane and P,P'-bis(9-phosphabicyclononyl)-hydrocarbons in which the smallest P-containing ring contains at least 5 carbon atoms. Such ligands include 9-aryl-9-phosphabicyclo[4.2.1]nonanes, 9-(dialkylaryl)-9-phosphabicyclo[4.2.1]nonanes, 9-alkyl-9-phosphabicyclo[4.2.1]nonanes, 9-cycloalkyl-9-phosphabicyclo[4.2.1]nonanes, 9-cycloalkenyl-9-phosphabicyclo-

[4.2.1]nonanes, P,P'-bis(9-phosphabicyclononyl)alkanes and their [3.3.1] isomers. Specific examples of such ligands are 9-phenyl-9-phosphabicyclo[4.2.1]nonane, 9-(2,4-dimethylphenyl)-9-phosphabicyclo[4.2.1]nonane, 9-ethyl-9-phosphabicyclo[4.2.1]nonane, 9-cyclohexyl-9-phosphabicyclo[4.2.1]nonane, 9-cyclopentenyl-9-phosphabicyclo[4.2.1]nonane, 1,2-P,P'-bis(9-phosphabicyclo[4.2.1]nonyl)ethane, 1,3-P,P'-bis(9-phosphabicyclo[4.2.1]nonyl)propane, 1,4-P,P'-bis(9-phosphabicyclo[4.2.1]nonyl)butane and their [3.3.1] isomers.

The reaction conditions of the hydroformylation may be selected from wide ranges. For example, temperatures may be from 20 °C to 300 °C. Temperatures in the range of from 150 °C to 250 °C, in particular from 125 to 200 °C, are generally recommended. Reaction pressures in the range of from 1000 to 20000 kPa a (10 to 200 bara) are typical, but lower or higher pressures may be selected. Reaction pressures in the range of from 2000 to 10000 kPa a (20 to 100 bara) are preferred. Molar ratios of catalyst to olefin ranging from 1:1000 to 1:1 are suitable. The ratio of hydrogen to carbon monoxide may be selected from wide ranges, but is usually above 1 to favour the formation of alcohol product. Preferably this molar ratio is in the range of from 2 to 10.

The hydroformylation process may or may not be carried out in the presence of an inert solvent. A variety of solvents may be applied, for example ketones such as acetone, methyl ethyl ketone, methyl isobutyl ketone, acetophenone and cyclohexanone; aromatic compounds such as benzene, toluene and the xylenes; halogenated aromatic hydrocarbons such as chlorobenzene and orthodichlorobenzene; halogenated paraffinic hydrocarbons such as methylene chloride and carbon tetrachloride; saturated hydrocarbons such as hexane,

- 20 -

heptane, methylcyclohexane and isooctane; and nitriles such as benzonitrile and acetonitrile.

Usual methods may be applied for work-up and to achieve product stabilisation and purification. To this  
5 end, methods such as distillation, extraction, hydrolysis and reduction may be applied. The reduction may be a hydrogen treatment using a catalyst of nickel on an alumina carrier or reduction with for example sodium borohydride. The product stabilisation may aim at  
10 removal of acetals by hydrolysis and of aldehydes by reduction.

The hydroformylation in accordance with this invention yields typically a branched primary alcohol composition comprising alcohols having a carbon number in  
15 the range of from 8 to 36, of which alcohols at least a portion of the molecules is branched, the average number of branches per molecule being at least 0.7 and the branching comprising methyl and optionally ethyl branches. Preferably, the branched primary alcohol  
20 composition comprises alcohols having a carbon number in the range of from 11 to 19. Preferably at least 75%w, more preferably at least 90%w, of the branched primary alcohol composition consists of alcohols having a carbon number in the range of from 11 to 19. In practice,  
25 frequently at most 99.99%w, more frequently at most 99.9%w, of the branched primary alcohol composition consists of alcohols having a carbon number in the range of from 11 to 19. When it is intended to prepare surfactant sulphates from the branched primary alcohol  
30 composition it is preferred that the branched primary alcohol composition comprises branched primary alcohols having a carbon number in the range of from 15 to 18, in which case preferably at least 75%w, more preferably at least 90%w, of the branched primary alcohol composition  
35 consists of alcohols having a carbon number in the range

- 21 -

of from 15 to 18. In practice, frequently at most 99.99%w, more frequently at most 99.9%w, of the branched primary alcohol composition consists of alcohols having a carbon number in the range of from 15 to 18.

5           Suitably the average number of branches per alcohol molecule present in the branched primary alcohol composition is at least 0.8, and preferably at least 0.9, for example 1.0. Suitably the average number of branches is at most 2.0, preferably at most 1.5, and in particular  
10           at most 1.4. The number of methyl branches is suitably at least 20%, more suitably at least 40%, preferably at least 50% of the total number of branches. In practice the number of methyl branches is frequently at most 99%, more frequently at most 98% of the total number of  
15           branches. If present, the number of ethyl branches is suitably at least 0.1%, in particular at least 1%, more in particular at least 2% of the total number of branches. Suitably, the number of ethyl branches is at most 20%, in particular at most 15%, more in particular  
20           at most 10% of the total number of branches. The number of any branches, if present, other than methyl and ethyl branches, may be less than 10%, in particular less than 5% of the total number of branches. The number of any  
25           branches, if present, other than methyl and ethyl branches, may be more than 0.1%, typically more than 1% of the total number of branches.

          The number of quaternary aliphatic carbon atoms is preferably low. For applications where biodegradability is not as critical, the number of quaternary aliphatic  
30           carbon atoms is suitably less than 2% of the carbon atoms present, more suitably less than 1%. For any application, and particularly for applications where biodegradability is important, the number of quaternary aliphatic carbon atoms preferably is 0.5 % or less, most  
35           preferably less than 0.5 %, and in particular less than

- 22 -

0.3%. In practice the number of quaternary aliphatic carbon atoms is frequently more than 0.01% of the aliphatic carbon atoms present, more frequently more than 0.05%.

5           The content of branched primary alcohols of the branched primary alcohol composition is typically at least 70%w, more typically at least 90%w, preferably at least 95%w, more preferably at least 99%w, in particular at least 99.9%w, relatively to the weight of the branched  
10       primary alcohol composition. In practice the content of branched primary alcohols is frequently at most 99.99%w, more frequently at most 99.95%w, relatively to the weight of the branched primary alcohol composition. The content of linear alcohols of the branched primary alcohol  
15       composition is typically at most 30%w, more typically at most 10%w, preferably at most 5%w, more preferably at most 1%w, in particular at most 0.1%w, relatively to the weight of the branched primary alcohol composition. In practice the content of linear alcohols is frequently at  
20       least 0.01%w, more frequently at least 0.05%w, relatively to the weight of the branched primary alcohol composition.

          The branched alcohols may be directly sulphated, or first oxyalkylated followed by sulphation.

25       Any technique known for sulphating alcohols may be used in this invention. For example, sulphation processes suitable for application in the present invention are known from US-A-3462525, US-A-3428654, US-A-3420875, US-A-3506580, US-A-3579537 and US-A-3524864. Suitable  
30       sulphation procedures include sulphation by reaction with oleum, sulphur trioxide (SO<sub>3</sub>), chlorosulphonic acid (ClSO<sub>3</sub>H) or sulphamic acid (NH<sub>2</sub>SO<sub>3</sub>H).

          When oleum is used, the concentration of sulphur trioxide in sulphuric acid is typically from 1 to 30%w,  
35       preferably from 2 to 20%w, based on the weight of the

- 23 -

oleum. Suitable amounts of sulphur trioxide are generally in the range of from 0.3 to 1.3 moles per mole of branched alcohols, preferably from 0.4 to 1.0 moles per mole of branched alcohols. The sulphation may be  
5 conducted by contacting the branched alcohols and the oleum at a temperature in the range of from 20 °C to 70 °C.

A typical sulphur trioxide sulphation procedure includes contacting liquid alcohol or its ethoxylate and  
10 gaseous sulphur trioxide in the reaction zone of a falling film sulphator cooled by water at a temperature in the range of from 20 °C to 70 °C to yield the sulphuric acid ester of alcohol or its ethoxylate. The reaction is suitably carried out at atmospheric pressure,  
15 for example at a pressure in the range of from 80 to 120 kPa a (0.8 to 1.2 bara). The sulphuric acid ester of the alcohol or its ethoxylate then exits the falling film column and is neutralised with a base, e.g., sodium or potassium hydroxide, to form the corresponding alcohol  
20 sulphate salt or the corresponding alcohol ethoxysulphate salt.

Suitable oxyalkylated alcohols may be prepared by adding to the branched alcohols an amount, for example, from 0.1 to 0.6%w, preferably from 0.1 to 0.4%w, based on  
25 the weight of the branched alcohols, of a strong base, typically an alkali metal or alkaline earth metal hydroxide such as sodium hydroxide or potassium hydroxide, which serves as a catalyst for oxyalkylation. The resulting mixture is dried, as by vapour phase  
30 removal of any water present, and an amount of alkylene oxide calculated to provide from 1 to 12 moles of alkylene oxide per mole of alcohol is then introduced. The resulting mixture may be allowed to react until the alkylene oxide is consumed. The course of the reaction



- 24 -

may be followed by following the decrease in the reaction pressure.

Suitable alkylene oxides are for example ethylene oxide, 1,2-propylene oxide, 1,2-butylene oxide and 2,3-butylene oxide. Ethylene oxide and 1,2-propylene oxide are preferred alkylene oxides. Two or more alkylene oxides may be added as a mixture to the reaction mixture alcohol, or sequentially to make a block structure. The oxyalkylation is typically conducted at elevated temperatures and pressures. Suitable reaction temperatures range of from 120 °C to 220 °C, with the range of from 140 °C to 160 °C being preferred. A suitable reaction pressure is achieved by introducing to the reaction vessel the required amount of alkylene oxide which has a high vapour pressure at the desired reaction temperature. For consideration of process safety, the partial pressure of the alkylene oxide reactant is preferably limited, for instance, to less than 500 kPa a (5 bara), and/or the reactant is preferably diluted with an inert gas such as nitrogen, for instance, to a vapour phase concentration of 50% or less. The reaction can, however, be safely accomplished at greater alkylene oxide concentration, greater total pressure and greater partial pressure of alkylene oxide if suitable precautions, known to the art, are taken to manage the risks of explosion. With respect to ethylene oxide, a total pressure of from 400 to 1000 kPa a (4 to 10 bara), with an ethylene oxide partial pressure of from 200 to 600 kPa (2 to 6 bara), is preferred, while a total pressure of from 500 to 800 kPa a (5 to 8 bara), with an ethylene oxide partial pressure of from 250 to 500 kPa a (2.5 to 5 bara), is more preferred. In the cases that the pressure serves as a measure of the degree of the reaction these pressure ranges relate to initial pressures. In such cases the

- 25 -

reaction is considered to be substantially complete when the pressure no longer decreases with time.

It should be understood that the oxyalkylation procedure serves to introduce a desired average number of alkylene oxide units per mole of branched alcohol oxyalkylate. For example, treatment of branched alcohols with 3 moles of ethylene oxide per mole of branched alcohol serves to effect the ethoxylation of each alcohol molecule with an average of 3 ethylene oxide moieties per mole alcohol moiety, although a substantial proportion of alcohol moieties will become combined with more than 3 ethylene oxide moieties and an approximately equal proportion will have become combined with less than 3. In a typical ethoxylation product mixture, there may also be a minor proportion of unreacted alcohol.

The general class of surfactant sulphates which may be made in accordance with this invention may be characterized by the chemical formula  $(R-O-A_x-SO_3)_nM$ , wherein R represents a moiety of the branched primary alcohols according to this invention which have a carbon number in the range of from 8 to 36, in particular from 11 to 19, more in particular from 15 to 18; A represents a moiety of an alkylene oxide; x represents the average number of moieties A per moiety R and is in the range of from 0 to 15; M is a cation selected from an alkali metal ion, an alkaline earth metal ion, an ammonium ion, and mixtures thereof; and n is a number depending on the valency of the cation(s) M, such that the total electrical charge is zero. The ammonium ion may be derived from an organic amine having 1, 2 or 3 organic groups attached to the nitrogen atom. Suitable ammonium ions are derived from monoethanol amine, diethanol amine and triethanol amine. It is preferred that the ammonium ion is of the formula  $NH_4^+$ . In preferred embodiments M

- 26 -

represents potassium or magnesium, as potassium ions can promote the water solubility of the (branched-alkyl)arylsulphonates and magnesium can promote their performance in soft water.

5 Preferred classes of surfactant sulphates comprise the alkali metal sulphates of the branched primary alcohols according to this invention which have a carbon number in the range of from 11 to 19, in particular from 15 to 18, and the alkali metal sulphates of the  
10 condensation product of the branched primary alcohols having a carbon number in the range of from 11 to 19, in particular from 15 to 18, with ethylene oxide and 1,2-propylene oxide, in which condensation product the number of ethoxy groups ranges from 3 to 12 and the ratio ethoxy  
15 groups to 1,2-propoxy groups is from 4 to 12.

The surfactants which can be made in accordance with this invention, in particular the surfactant sulphates, may be used as surfactants in a wide variety of applications, including detergent formulations such as  
20 granular laundry detergent formulations, liquid laundry detergent formulations, liquid dishwashing detergent formulations; and in miscellaneous formulations such as general purpose cleaning agents, liquid soaps, shampoos and liquid scouring agents.

25 The surfactant sulphates find particular use in detergent formulations, specifically laundry detergent formulations. These formulations are generally comprised of a number of components, besides the surfactant sulphates themselves: other surfactants of the ionic,  
30 nonionic, amphoteric or cationic type, builders, cobuilders, bleaching agents and their activators, foam controlling agents, enzymes, anti-greying agents, optical brighteners, and stabilisers.

The present liquid laundry detergent formulations  
35 may comprise the same components as the granular laundry

- 27 -

detergent formulations, but they generally contain less of the inorganic builder component. Hydrotropes may be present in the liquid detergent formulations. General purpose cleaning agents may comprise other surfactants, builders, foam control agents, hydrotropes and solubiliser alcohols.

The present formulations may contain a large amount of the builder and cobuilder components, in amounts up to 90w%, preferably between 5 and 35w%, based on the weight of the formulation, to intensify the cleaning action. Examples of common inorganic builders are phosphates, polyphosphates, alkali metal carbonates, silicates and sulphates. Examples of organic builders are polycarboxylates, aminocarboxylates such as ethylenediaminetetraacetates, nitrilotriacetates, hydroxycarboxylates, citrates, succinates and substituted and unsubstituted alkanedi- and polycarboxylic acids. Another type of builder, useful in granular laundry and built liquid laundry agents, includes various substantially water-insoluble materials which are capable of reducing the water hardness e.g. by ion exchange processes. In particular the complex sodium aluminosilicates, known as type A zeolites, are very useful for this purpose.

The present formulations may also contain percompounds with a bleaching action, such as perborates, percarbonates, persulphates and organic peroxy acids. Formulations containing percompounds may also contain stabilising agents, such as magnesium silicate, sodium ethylenediaminetetraacetate or sodium salts of phosphonic acids. In addition, bleach activators may be used to increase the efficiency of the inorganic persalts at lower washing temperatures. Particularly useful for this purpose are substituted carboxylic acid amides, e.g.

- 28 -

tetraacetylenediamine, substituted carboxylic acids, e.g. isononyloxybenzenesulphonate and sodium-cyanamide.

Examples of suitable hydrotropic substances are alkali metal salts of benzene, toluene and xylene  
5 sulphonic acids; alkali metal salts of formic acid, citric and succinic acid, alkali metal chlorides, urea, mono-, di-, and triethanolamine. Examples of solubiliser alcohols are ethanol, isopropanol, mono- or polyethylene glycols, monopropylene glycol and etheralcohols.

10 Examples of foam control agents are high molecular weight fatty acid soaps, paraffinic hydrocarbons, and silicon containing defoamers. In particular hydrophobic silica particles are efficient foam control agents in these laundry detergent formulations.

15 Examples of known enzymes which are effective in the laundry detergent formulations are protease, amylase and lipase. Preference is given to the enzymes which have their optimum performance at the design conditions of the washing and cleaning agent.

20 A large number of fluorescent whiteners are described in the literature. For the laundry washing formulations, the derivatives of diaminostilbene disulphonates and substituted distyrylbiphenyl are particularly suitable.

25 As antigreying agents, water soluble colloids of an organic nature are preferably used. Examples are water soluble polyanionic polymers such as polymers and copolymers of acrylic and maleic acid, cellulose derivatives such as carboxymethyl cellulose methyl- and  
30 hydroxyethylcellulose.

The surfactants which can be made in accordance with this invention, in particular the surfactant sulphates, may also advantageously be used in personal care products, in enhanced oil recovery applications and for

- 29 -

the removal of oil spillage offshore and on inland waterways, canals and lakes.

The formulations according to the invention typically comprise one or more inert components. For instance, the balance of liquid detergent formulations is typically an inert solvent or diluent, most commonly water. Powdered or granular detergent formulations typically contain quantities of inert filler or carrier materials.

As used herein, the average number of branches per molecule, further particulars of the type and position of branching and the content of quaternary aliphatic carbon atoms are as defined in US-A-5849960 and they are determined by the methods as described in US-A-5849960. Also the further analytical methods and the test methods are as described in US-A-5849960.

Unless specified otherwise, the low-molecular weight organic compounds mentioned herein have typically at most 40 carbon atoms, more typically at most 20 carbon atoms, in particular at most 10 carbon atoms, more in particular at most 6 carbon atoms. Organic compounds are deemed to be compounds which comprise carbon atoms and hydrogen atoms in their molecules. The group of low-molecular weight organic compounds does not include polymers and enzymes.

As defined herein, ranges for numbers of carbon atoms (i.e. carbon number) include the numbers specified for the limits of the ranges. Number of carbon atoms as defined herein include the carbon atoms along the carbon backbones, as well as branching carbon atoms, if any.

The following example will illustrate the nature of the invention without its scope.

- 30 -

Example 1 (prophetic)

A Fischer Tropsch hydrocarbon mixture of linear paraffins having at least 5 carbon atoms, further comprising a minor quantity of oxygenates, is subjected to conditions of hydrocracking and hydroisomerisation by contacting the hydrocarbon mixture, in the presence of hydrogen, with a palladium on silica-alumina catalyst (0.5%w Pd, 55%w Al<sub>2</sub>O<sub>3</sub>, 45%w SiO<sub>2</sub>) at a temperature of 350°C and at a pressure of 6000 kPa a (60 bara), applying a liquid hourly space velocity of 0.5 l/l/h and a hydrogen to wax feed ratio of 400 Nl/l (liquid volumes at room temperature, "Nl" refers to the gas volume at 0 °C, 100 kPa (1 bar)).

The hydrocracking/hydroisomerisation product stream is fractionated by distillation and by separation over a molecular sieve zeolite 5A such that an isoparaffinic composition is obtained which consists of branched and linear paraffins having a carbon number in the range of from 14 to 17. The average number of branches is 1.9 per paraffin molecule. The number of methyl branches is 60% of the total number of branches. The number of ethyl branches is 15% of the total number of branches. The quantity of branched paraffins present in the isoparaffinic composition is more than 96%w, and the quantity of linear paraffins present in the isoparaffinic composition is less than 4%w, based on the weight of the isoparaffinic composition.

The isoparaffinic composition is subjected to conditions of dehydrogenation by contacting the isoparaffinic composition, in the presence of hydrogen, with a platinum on gamma alumina catalyst (0.5%w platinum) at a temperature of 490 °C and at a pressure of 250 kPa a (2.5 bara), applying in the feed a hydrogen/paraffins molar ratio of 4. The residence time

- 31 -

of the isoparaffinic composition is controlled such that the conversion is 15%.

The dehydrogenation product is fractionated by separation over a molecular sieve zeolite 5A to remove  
5 paraffins. A paraffin free olefin fraction is obtained.

The olefin fraction is hydroformylated by reacting the olefin fraction with hydrogen and carbon monoxide at a molar ratio of hydrogen to carbon monoxide of 1.7:1 in the presence of a phosphine modified cobalt catalyst at a  
10 temperature of 185 °C and at a pressure of 8000 kPa a (80 bara) until completion of the reaction.

The hydroformylation reaction product is subjected to usual treatments for deactivating the hydroformylation catalyst, and stabilising, purifying and drying the  
15 alcohol product obtained.

The alcohol product is then sulphated by a known method.

#### Example 2 (prophetic)

The procedure of example 1 is repeated, except that  
20 the separation over a molecular sieve is omitted, and that the quantity of branched paraffins present in the isoparaffinic composition obtained is 80 %w and the quantity of linear paraffins present in the isoparaffinic composition obtained is 20 %w, based on the weight of the  
25 isoparaffinic composition, and in the isoparaffinic composition obtained the average number of branches is 1.5 per paraffin molecule. In other aspects the isoparaffinic composition is as indicated in example 1.

#### Example 3 (prophetic)

30 The procedure of example 1 is repeated, except that the Fischer Tropsch hydrocarbon mixture consists essentially of a wax of linear paraffins having at least 30 carbon atoms. The isoparaffinic composition obtained is of a similar composition as specified in example 1.



- 32 -

Example 4 (prophetic)

The procedure of example 3 is repeated, except that the separation over a molecular sieve is omitted, the quantity of branched paraffins present in the isoparaffinic composition obtained is 90%w, the quantity of linear paraffins present in the isoparaffinic composition obtained is 10%w, based on the weight of the isoparaffinic composition, and in the isoparaffinic composition obtained the average number of branches is 1.7 per paraffin molecule. In other aspects the isoparaffinic composition is as indicated in example 1.

Examples 5-8 (prophetic)

The procedures of examples 1-4 are repeated, except that in each case the isoparaffinic composition obtained consists of branched and linear paraffins having a carbon number in the range of from 13 to 17, instead of from 14 to 17. In other aspects the isoparaffinic compositions obtained are as indicated in the respective example of examples 1-4.

Example 9

C<sub>9-24</sub> paraffins produced by polymerisation using methane and syn gas (H<sub>2</sub> and CO) as starting materials were separated by distillation. A sample of C<sub>15</sub>-C<sub>16</sub> paraffins was dehydrogenated essentially using known dehydrogenation/olefin extraction processes, to produce C<sub>15</sub>-C<sub>16</sub> branched olefin ("candidate olefins").

A control olefin feed, which typically has a quaternary carbon content of 0.20 or less was C<sub>15</sub>-C<sub>16</sub> branched olefins obtained by isomerisation of linear internal olefins ("ISO olefins"). The isomerisation of the control was conducted essentially as described in Example 2 of US-A-5849960. The candidate olefins and the ISO olefins had the following characteristics:

- 33 -

Table 1. Olefin Feed

Olefin type	ISO olefins	Candidate olefins
Olefin, %wt	98.3	62
Paraffin, %wt	1.7	25
Aromatics, %wt	0	13

C<sub>16</sub>-C<sub>17</sub> branched alcohols were synthesised from the  
 olefin samples by hydroformylation substantially as  
 described in US-A-5849960. Procedures performed in  
 parallel (same conditions and procedures) were used to  
 convert the ISO olefins to C<sub>16</sub>-C<sub>17</sub> branched alcohols (ISO  
 alcohols, D in Table 4 below) in order to provide  
 comparison data for the candidate sample (E in Table 4  
 below).

The progress of the reaction was monitored by syn  
 gas uptake. The isolation and purification steps  
 consisted of a vacuum flash separation to remove heavy  
 ends and catalyst residues from the crude alcohol, a  
 sodium borohydride (NaBH<sub>4</sub>) treatment to reduce formate  
 esters and aldehydes to alcohols, a water wash step (3  
 times) to remove the unreacted borohydride and decomposed  
 borate compounds; and a vacuum fractional distillation to  
 isolate alcohols from unreacted olefins, side product  
 paraffins, and any residual catalyst and heavy ends. The  
 reduction of aldehydes and formate esters during the  
 sodium borohydride treatment was monitored by FTIR.

The candidate alcohol exhibited a branching index of  
 1.5 and an average carbon number of 16.1. The following  
 results for the candidate alcohols were observed:

Table 2.

Alcohol End Branching Analysis (C-1 refers to alcohol carbon)	
%no branching or branching at the C4+ position	72.0
% branching at the C3 position	11.7

- 34 -

% methyl branching at the C2 position	6.7
% ethyl branching at the C2 position	1.4
% propyl or greater branching at the C2 position	8.3

## %Overall Type of Branching

C1 (methyl)	60.7
C2 (ethyl)	7.6
C3+ (propyl+)	31.6

The control showed the following results:

Table 3.

Alcohol End Branching Analysis (C-1 refers to alcohol carbon)

%no branching or branching at the C4+ position	63.6
% branching at the C3	21.8
% methyl branching at the C2	4.8
% ethyl branching at the C2	1.3
% propyl or greater branching at the C2 position	8.6

## %Overall Type of Branching

C1 (methyl)	79.9
C2	10.0
C3+ (propyl+)	10.1

5

The carbon number distribution was determined using the Nitric Oxide Townsend Discharge Chemical Ionization Gas Chromatography/Mass Spectrometry method described in I. Dzidic, et al, Analytical Chemistry, Vol 64, pp. 2227-2232 (1992). The results were as shown in the following Table:

10

- 35 -

Table 4. Carbon Number Distribution and

	D (ISO alcohols)				E (Candidate alcohols)		
	% Br alcohol	% Ln alcohol	CND		% Br alcohol	% Ln alcohol	CND
C14	0.1	0.0	0.1		0.0	0.0	0.0
C15	0.7	0.4	1.1		0.7	3.0	3.7
C16	26.5	1.0	27.5		33.9	14.7	48.6
C17	66.7	0.9	67.5		38.5	0.8	39.3
C18	3.4	0.0	3.4		7.8	0.0	7.8
C19	0.4	0.0	0.4		0.5	0.0	0.5
total	97.8	2.2	100.0		81.5	18.5	100.0

Note: The amount of linear alcohol is calculated based on calibration of pure standard compounds. However due to lack of suitable standards for branched components, the distribution of branched alcohol is calculated assuming equal response for all components. The resulting distribution may be close but not totally accurate.

The "Alcohol End Branching Analysis (C-1 refers to alcohol carbon)" box describes branching in the molecule as it pertains to the location of such branches relative to the alcohol end of the molecule. When branching is present next door to the alcohol carbon (C2 carbon), the NMR is able to actually differentiate between, methyl, ethyl and propyl or longer branch types. When branching is on the carbon two away from the alcohol carbon (C3), NMR can only tell that there is a branch but cannot tell if it is a methyl, an ethyl or a propyl or longer. By the time you are three bonds away from the alcohol carbon, the NMR cannot tell if there is any kind of branching. So, the entry "%no branching or branching at the C4+ position" coadds linear molecules as well as molecules that have branching 3+ bonds away from the alcohol carbon.

The "%Overall Type of Branching" box gives the amounts of C1 (methyl), C2 (ethyl) and C3+ (propyl or longer) branches in the molecule irrespective of where these branches might occur relative to the alcohol end.

NMR analysis of the candidate sample showed a quaternary carbon content below 0.5%. Molecules containing quaternary carbons are known to be difficult to biodegrade. Hence, a quaternary carbon content below 0.5% renders these materials very useful and quicker to

- 36 -

biodegrade.

The Co-hydroformylation rate was calculated from the syn gas uptake using the first hour of data. Several fractions were collected during the distillation and analysed by GC-FID and FT-IR. The last two fractions of candidate alcohol (E) collected during the distillation solidified at room temperature, reference (D) sample remained in the liquid state.

#### Example 10

Using the procedures described in Example 9, the quaternary carbon content of alcohol molecules found in a competitive product were measured. The competitive product was a highly methyl branched alcohol prepared by oligomerisation of propylene followed by hydroformylation, which converted the olefin into a highly methyl branched alcohol. The quaternary carbon content was approximately 0.6. US-A-5112519 describes this product as "a highly methyl branched tridecyl alcohol known for its use in lubricants and detergent formulations which does not require rapid biodegradation."

#### Example 11

Sulphates of D and E from Example 9 were prepared by chlorosulphation and analysed. The following were the results:

Source	% AM	UOM	H2O	Sulphate	Total
D (Ex. 9)	28.8	1.4	65.6	0.82	96.6
E (Ex. 9)	30.9	1.3	62.8	0.73	95.7

AM = Active Matter

UOM = Unreacted Organic Matter

It is apparent that certain features of the

- 37 -

invention, which are for clarity described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, features of the invention which are described in the context of a  
5 single embodiment may also be provided separately or in any suitable sub-combination.

- 38 -

C L A I M S

1. A process for preparing branched olefins, which process comprises dehydrogenating an isoparaffinic composition comprising 0.5% or less quaternary aliphatic carbon atoms over a suitable catalyst, which isoparaffinic composition comprises paraffins having a carbon number in the range of from 7 to 35, of which paraffins at least a portion of the molecules is branched, the average number of branches per paraffin molecule being from 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, which isoparaffinic composition has been obtained by hydrocracking and hydroisomerisation of a paraffinic wax, said branched olefins having a quaternary carbon content of 0.5% or less.
2. A process as claimed in claim 1, wherein the content of branched paraffins of the isoparaffinic composition is at least 70 %w relative to the weight of the isoparaffinic composition.
3. A process of using olefins for making an anionic surfactant, a nonionic surfactant or a cationic surfactant, in particular a surfactant sulphate or sulphonate, comprising converting branched olefins into the surfactant which branched olefins have been obtained by a process as claimed in claim 1 or 2.
4. A process for preparing alcohol sulphates comprising converting branched olefins into branched alcohol sulphates, which branched olefins have been obtained by a process which comprises dehydrogenating an isoparaffinic composition comprising 0.5% or less quaternary aliphatic carbon atoms over a suitable catalyst, which isoparaffinic composition comprises paraffins having a

- 39 -

carbon number in the range of from 7 to 35, of which paraffins at least a portion of the molecules is branched, the average number of branches per paraffin molecule being from 0.7 to 2.5 and the branching  
5 comprising methyl and optionally ethyl branches, said alcohol sulphates comprising 0.5% or less quaternary aliphatic carbon atoms.

5. A process as claimed in claim 3 or 4, wherein the branched olefins are converted into the branched alcohols  
10 by reacting the branched olefins with carbon monoxide and hydrogen in the presence of a suitable catalyst.

6. A branched olefin composition having 0.5% or less quaternary carbon atoms and comprising olefins having different, consecutive carbon numbers in the range of  
15 from 7 to 35, of which olefins at least a portion of the molecules is branched, the average number of branches per molecule being 0.7 to 2.5 and the branching comprising methyl and optionally ethyl branches, and which branched olefin composition is obtainable by a process which  
20 comprises dehydrogenating an isoparaffinic composition which has been obtained by hydrocracking and hydroisomerisation of a paraffinic wax, said isoparaffinic composition comprising less than 0.5% quaternary aliphatic carbon atoms.

25 7. A branched alcohol composition which is obtainable by a process as claimed in claim 5.

8. An anionic surfactant, a nonionic surfactant or a cationic surfactant which is obtainable by a process as claimed in any one of claims 3 to 5.

30 9. An isoparaffinic composition comprising less than 0.5% quaternary aliphatic carbon atoms and comprising paraffins having different, consecutive carbon numbers in the range of from 7 to 35, of which paraffins at least a portion of the molecules is branched, the average number  
35 of branches per paraffin molecule being from 0.7 to 2.5



- 40 -

and the branching comprising methyl and optionally ethyl branches.

10. A branched olefin composition which is obtainable by a process as claimed in any one of claims 1 to 3.